

D.C. Power Supply

Patent No: 81011



FEATURES :

- * **0.01% High Regulation**
- * **Constant Voltage and Constant Current Operation**
- * **Low Ripple and Noise**
- * **Overload and Reverse Polarity Protection**
- * **3 1/2 Digits 0.5" LED Display**
- * **Application for Material and Products Aging**
- * **Built-in Overvoltage and Overcurrent Tripped Crowbar**
- * **Ten-turn Potentiometer**

GPR-U SERIES (DIGITAL TYPE)

SPECIFICATIONS

SPECIFICATIONS		
CONSTANT VOLTAGE OPERATION	Regulation Ripple & Noise Recovery Time Output Range	Line regulation $\leq 0.01\% + 3mV$ Load regulation $\leq 0.01\% + 5mV (<10A)$ $\leq 0.02\% + 5mV \text{ rating} \geq 10A$ $\leq 2mV_{rms} \text{ } 5Hz \sim 1MHz$ $\leq 100mS$ (50% Load change, Minimum load 0.5A) 0 to rating voltage continuously adjustable
CONSTANT CURRENT OPERATION	Regulation Ripple Current Output Range	Line regulation $\leq 0.2\% + 3mA$ Load regulation $\leq 0.2\% + 3mA$ $\leq 5mArms (<20A), \leq 20mArms (<50A), \leq 100mArms (<100A)$ 0 to rating amperes continuously adjustable
METER	Digital	3 1/2 Digits 0.5" LED display Accuracy $\pm (0.5\% \text{ of rdg } + 2 \text{ digits })$
INSULATION	Chassis and Terminal Chassis and AC Cord	100MW or above (DC 1000V) 100MW or above (DC 1000V)
POWER SOURCE		AC 120V $\pm 10\%$, 50/60Hz (AC220V, or 240V order made)
ACCESSORIES		Instruction manual x 1 Test lead GTL-105 x 1 ($\leq 3A$) or GTL-104 x 1 ($\leq 10A$) or Not Available > 10A or 600V
DIMENSIONS		430(W) x 178(H) x 572(D) mm

	Model	Output Volts (V)	Output Amps (A)	Weight (kg)
Digital	GPR-0875HD	0 ~ 8	0 ~ 75	29
	GPR-1850HD	0 ~ 18	0 ~ 50	30
	GPR-3520HD	0 ~ 35	0 ~ 20	29.5
	GPR-6015HD	0 ~ 60	0 ~ 15	30
	GPR-7510HD	0 ~ 75	0 ~ 10	29.5
	GPR-16H50D	0 ~ 160	0 ~ 5	30.5
	GPR-25H30D	0 ~ 250	0 ~ 3	29.5
	GPR-35H20D	0 ~ 350	0 ~ 2	29.5
	GPR-50H15D	0 ~ 500	0 ~ 1.5	29.5
	GPR-60H15D	0 ~ 600	0 ~ 1.5	30.5
	GPR-100H05D	0 ~ 1000	0 ~ 0.5	28.5

NOTE: Welcome special order from 8 volts to 1000 volts and 0.5 Amps to 75 Amps under 1kVA available.