



E4400A Analog RF Signal Generator, 250 kHz to 1000 MHz (Discontinued - Support Information Only)

Data Sheet

Frequency Specifications

Frequency Range Agilent ESG-1000A: 250 kHz to 1000 MHz

Resolution: 0.01 Hz

Switching Speed Modulation On: <45 ms, typical Modulation Off: <35 ms, typical

Accuracy: Same as timebase Sweep Modes

Operating modes Step: frequency & power, and arbitrary list

Dwell Time: 2 ms to 60 sec

Number of Points: 2 to 401 Internal Reference Oscillator

Stability Standard (typical) High Stability (Opt 1E5) Aging Rate <±2 ppm/yr <±0.1 ppm/yr or <± 0.0005 ppm/day after 45 days

Temperature <±1 ppm <±0.05 ppm, typical (0 ° to 55 °C)

Line Voltage <±0.1 ppm <±0.002 ppm, typical (+5%, -10%) (+5%, -10%)

Timebase Reference Output Frequency: 10 MHz Amplitude: >0.35 V_{rms} into 50 ohm load

External Reference Input Frequency: 1, 2, 5, 10 MHz ± typ. 10 ppm Option 1E5: 1 ppm, typical Amplitude: >0.15 V_{rms} Input Impedance: 50 ohm Output

Range 250 kHz to 1000 MHz: +13 to -136 dBm

Resolution 0.02 dB

Level Accuracy¹ (at 23 ±5°C) +7 to -127 dBm <-127 dBm 250 kHz to 1 GHz: ±0.5 dB ±1.5 dB

Attenuator Hold Level Range: >17 dB

Switching Speed: <25 ms typical With Power Search Mode: <210 ms typical

Reverse Power Protection: 250 kHz to 1000 MHz: 50 Watts Max dc Voltage: 50 V

SWR (typical) 250 kHz to 1000 MHz: <1.4:1

Output Impedance: 50 ohms ¹Accuracy degrades by 0.02 dB/°C over full temperature range and by 0.3 dB above + 7 dBm. Frequency Bands

Band Frequency Range N# 1 250 kHz to <=249.999 MHz 1 2 >249.999 to <=500 MHz 0.5 3 >500MHz to <=1 GHz 1

Spectral Purity

SSB Phase Noise (typical, at 20 kHz offset) at 500 MHz: <-120 dBc/Hz at 1000 MHz: <-116 dBc/Hz

Residual FM (CW mode, 0.3-3 kHz BW, CCITT, rms): Phase Noise Mode 1: <N x 2 Hz Phase Noise Mode 2: <N x 4 Hz

Harmonics <=+4 dBm output level: <-30 dBc

Nonharmonics (>3 kHz offset, <+7 dBm output level) 250 kHz to 1000 MHz: <-65 dBc

Subharmonics <=1000 MHz: None Frequency Modulation

Maximum Deviation: N x 10 MHz

Resolution: 0.1% of deviation or 1 Hz, whichever is greater

Deviation Accuracy(1 kHz rate, dev. <N x 100 kHz): <±(3.5% of FM deviation + 20 Hz)

Modulation Frequency Response(deviation = 100 kHz)

Path Rates 1 dB Bandwidth 3 dB Bandwidth, typical FM1 dc/20 Hz to 100 kHz dc/5 Hz to 10 MHz

FM2 dc/20 Hz to 100 kHz dc/5 Hz to 1 MHz



Agilent Technologies

Distortion (1 kHz rate, THD, dev. = N x 100 kHz): <1% Phase Modulation
Maximum Deviation: N x 90 radians
Resolution: 0.1% of set deviation
Deviation Accuracy (1 kHz rate): <±(5% of deviation +0.01 radians)
Modulation Frequency Response
PM Mode Maximum Rates (3 dB BW) Deviation PM1 PM2 Normal BW N x 90 rad dc to 100 kHz dc to 100 kHz
High BW N x 2 pi rad dc to 1.5 MHz (typ) dc to 1 MHz (typ) N x pi/2 rad dc to 4 MHz (typ) dc to 0.9 MHz (typ)
Distortion (1 kHz rate, THD, dev <N x 90 rad): <1% Amplitude Modulation fc>500 kHz
Range(envelope peak <=max specified power): 0 to 100%
Resolution: 0.1%
Rates (3 dB Bandwidth): dc/10 Hz to 10 kHz
Distortion(1 kHz rate, THD) 30% AM: <1.5% 90% AM: <4%
Accuracy(1 kHz rate): <±(5% of setting + 1%) Pulse Modulation
On/Off Ratio <=1 GHz: >80 dB
Rise/Fall Times: 150 ns, typical
Minimum Width (typical) ALC On: 2 μs ALC Off: 0.4 μs
Pulse Repetition Frequency (typical) ALC On: 10 Hz to 250 kHz ALC Off: DC to 1.0 MHz
Level Accuracy (relative to CW): ± 0.5 dB, typical
Internal Pulse Generator (Squarewave only) Squarewave Rates: 0.1 Hz to 50 kHz Pulse Period: 16 μs to 30 seconds
Width: 8 μs to 30 seconds Resolution: 4 μs Internal Modulation Source Provides FM, PM, and AM Modulation Signals and LF Out
Waveforms: sine, square, ramp, triangle, pulse, noise
Rate Range: Sine: 0.1 Hz to 50 kHz Square, Ramp, Triangle: 0.1 Hz to 10 kHz
Resolution: 0.1 Hz Pulse: 4 μs
Frequency Accuracy: 0.005%
Swept Sine Mode(Frequency, Phase Continuous):
Operating Modes: Triggered or Continuous Sweeps
Frequency Range: 0.1 Hz to 50 kHz
Sweep Time: 1 ms to 65 seconds
Resolution: 1 ms
Dual Sinewave Mode Frequency Range: 0.1 Hz to 50 kHz
Amplitude Ratio: 0 to 100%
Amplitude Resolution: 0.1% LF Out (Internal Modulation Source)
Amplitude: 0 to 3 V_{peak} into 50 ohms
Output Impedance: <1 ohm External Modulation Inputs
Modulation Types: Ext1: FM, PM, AM, and Burst Envelope Ext2: FM, PM, AM, and Pulse
Simultaneous Modulation All modulation types may be simultaneously enabled, except: FM with PM, AM with Burst. AM, FM, and PM can sum simultaneous inputs from any two sources (INT,EXT1, and EXT2.) Any given source (INT, EXT1, or EXT2) may only be routed to one activated modulation type. Remote Programming
Interface: HP-IB (IEEE-488.2-1987) with Listen and Talk, RS-232
Control Languages: SCPI version 1992.0, also compatible with Agilent 8656B & 8657A/B/D/J mnemonics
Functions Controlled: All front panel functions except power switch and knobs
IEEE-488 Functions: SH1, AH1, T6, TE0, L4, LE0, SR1, RL1, PP0, DC1, DT0, C0, E2

General Specifications

Power Requirements: 90 to 254 V; 50,60, or 400 Hz; 200 W maximum
Operating Temperature Range: 0 to 55° C
Leakage: Conducted and radiated interference meets MIL-STD-461B RE02 Part 2 and CISPR 11
Storage Registers: Up to 100 storage registers, up to 10 sequences available
Weight: <12.7 kg (28 lb) net, <21 kg (46 lb.) shipping
Dimensions: 133 mm H x 426 mm W x 432 mm D (5.25 in H x 16.8inW x 17 in D)