



[Home](#)
[Applications](#)
[Products](#)
[Where To Buy](#)
[What's New](#)
[Support](#)
[About Us](#)

Product Search

- Product Home
- Features
- Specifications**
- Models, Pricing, Options, Accessories
- Manuals
- Product Registration

Bench Instruments > Bench Multimeters >

Fluke 45 Dual Display Multimeter

General Specifications	
VDC	Range: 0V-1000V Resolution: 1 μ V-0.01V Best Accuracy: $\pm 0.025\% + 2^*$
VAC (True-rms, AC Coupled) Freq. 20 Hz-100 khz	Range: 0V-750V Resolution: 1 μ V-0.01V Best Accuracy: $\pm 0.2\% + 10^*$
dB Readout (600 Ω Ref.) (Ref. Z 2Ω-8000Ω)	Range: -34 \pm 60 Resolution: 0.01 dB-0.1 dB Best Accuracy: ± 0.08 dBm *
ADC	Range: 0 mA-10A Resolution: 0.1 μ A-10 mA Best Accuracy: $\pm 0.05\% + 2^*$
AAC (True-rms, AC Coupled) Freq. 20 Hz-20 khz	Range: 15 μ A-10A Resolution: 0.1 μ A-10 mA Best Accuracy: $\pm 0.5\% + 10^*$
Resistance	Range: 0 Ω -100 M Ω Resolution: 0.001 Ω -1m Ω Best Accuracy: $\pm 0.05\% + 2^*$
Frequency	Range: 5 Hz - 1 MHz Resolution: .01 Hz-1 kHz Best Accuracy: $\pm 0.05\% + 1^*$
Size	216 mm W x 93 mm H x 286 mm D (8.5" W x 3.67" H x 11.27" D)
Weight	Net 2.4 kg (5.2 lb); with battery 3.2 kg (7 lb)
One Year Warranty	One year calibration interval

*Medium reading rate

© 1995 - 2005 Fluke Corporation
[Privacy Statement](#)