

2001
2002

7½-Digit High Performance Multimeter 8½-Digit High Performance Multimeter



- True 7½- (Model 2001) or 8½-digit (Model 2002) resolution
- Exceptional measurement integrity with high speed
- Broad range of built-in measurement functions
- Built-in 10 channel scanner option
- IEEE-488.2 and SCPI compatible
- Model 2002 has HP 3458A emulation mode

High Accuracy ACV Measurements

A patented circuit design makes the 2001 and 2002's AC measurements several times more accurate than competitive DMMs, thus maintaining very good accuracy (better than 0.1%) down to 1Hz. The wide bandwidth of these DMMs allows for accurate measurements of high frequency AC signals without the need for a special AC meter. Both the 2001 and 2002 feature TRMS AC, Average AC, Peak AC, AC+DC, and Crest Factor measurement capability for a wide variety of applications.

Built-In Scanner (Multiplexer) Options

With the addition of a plug-in scanner card, it becomes a complete scan and measure system for applications involving up to ten measurement points. The additional resolution and measurement ranges provided by the 2002 make it an excellent choice for production test, design verification, and metrology applications where high accuracy is critical.



DMM users whose applications demand exceptional resolution, accuracy, and sensitivity combined with high throughput now have two attractive alternatives to high priced, high-end DMMs. Keithley's 7½-digit Model 2001 and 8½-digit Model 2002 High Performance Digital Multimeters not only deliver performance specifications usually associated only with instruments that cost thousands more, but they also offer a broad range of functions not typically available from DMMs.

True 7½- (or 8½-) Digit Resolution

While other DMMs may claim 7½- or 8½-digit resolution, those instruments must average multiple readings to extend their resolution. The resolution specifications of the 2001 and 2002 are based on a 28-bit A/D converter that provides the resolution needed to discern smaller changes. This higher resolution also provides greater dynamic range, making it possible to measure from 1µV to 20V on a single range, thus avoiding range-shift errors and delays.

High Throughput, High Accuracy DCV and Resistance Measurements

In applications where high throughput is critical, both the Model 2001 and 2002 provide more than 2000 readings per second at 4½-digit resolution. At 7½ digits, the Model 2002 maintains full rated accuracy at reading rates up to 44/second on DCV and ohms.

The Model 2002 uses a unique single-phase method for 4-wire ohms measurements. This makes it twice as fast for a given power line cycle rate. This also eliminates errors due to changing lead resistances that can result from fast test handlers. A built-in "open-lead" detection circuit also eliminates many production test problems.

ACCESSORIES AVAILABLE

TEST LEADS AND PROBES

5805	Kelvin Probes, 0.9m (3 ft)
8606	High Performance Modular Probe Kit

CABLES/ADAPTERS

7007-1	Shielded GPIB Cable, 1m (3.3 ft)
7007-2	Shielded GPIB Cable, 2m (6.6 ft)
7009-5	RS-232 Cable

RACK MOUNT KITS

4288-1	Single Fixed Rack Mount Kit
4288-4	Side by Side Rack Mount Kit

OTHER

KPCI-488	IEEE-488 Interface/Controller for the PCI Bus
KPC-488.2AT	IEEE-488 Interface Card for IBM PC/AT (full slot)

1.888.KEITHLEY (U.S. only)

www.keithley.com

KEITHLEY

A GREATER MEASURE OF CONFIDENCE

2001
2002

Ordering Information

2001 High Performance 7½-Digit DMM with 8K Memory

2001/MEM1
High Performance 7½-Digit DMM with 32K Memory

2001/MEM2
High Performance 7½-Digit DMM with 128K Memory

2002 High Performance 8½-Digit DMM with 8K Memory

2002/MEM1
High Performance 8½-Digit DMM with 32K Memory

2002/MEM2
High Performance 8½-Digit DMM with 128K Memory

2000-SCAN
10-Channel Scanner Card

2001-SCAN
10-Channel Scanner Card with two high-speed channels

2001-TCSCAN
9-Channel Thermocouple Scanner Card

These products are available with an Extended Warranty.

Accessories Supplied

Model 8605 High Performance Modular Test Leads, user's manual, option slot cover, and full calibration data.

For more information, request the Model 2001 and 2002 Technical Specifications books.

7½-Digit High Performance Multimeter
8½-Digit High Performance Multimeter

2001 Condensed Specifications

DC VOLTS		ACCURACY ±(ppm of reading + ppm of range)	
RANGE	RESOLUTION	INPUT RESISTANCE	90 Days
200 mV	10 nV	>10 GΩ	25 + 6
2 V	100 nV	>10 GΩ	18 + 2
20 V	1 μV	>10 GΩ	18 + 4
200 V	10 μV	10 MΩ ±1%	27 + 3
1000 V	100 μV	10 MΩ ±1%	31 + 6

RESISTANCE		ACCURACY ±(ppm of reading + ppm of range)	
RANGE	RESOLUTION	CURRENT SOURCE	90 Days
20 Ω	1 μΩ	9.2 mA	52 + 7
200 Ω	10 μΩ	0.98 mA	36 + 7
2 kΩ	100 μΩ	0.98 mA	33 + 4
20 kΩ	1 mΩ	89 μA	32 + 4
200 kΩ	10 mΩ	7 μA	72 + 4.5
2 MΩ	100 mΩ	770 nA	110 + 4.5
20 MΩ	1 Ω	70 nA	560 + 4.5
200 MΩ	10 Ω	4.4 nA	10000 + 100
1 GΩ	100 Ω	4.4 nA	20000 + 100

DC AMPS		ACCURACY ±(ppm of reading + ppm of range)	
RANGE	RESOLUTION	MAXIMUM BURDEN VOLTAGE	90 Days
200 μA	10 pA	0.25 V	300 + 25
2 mA	100 pA	0.31 V	300 + 20
20 mA	1 nA	0.4 V	300 + 20
200 mA	10 nA	0.5 V	300 + 20
2 A	100 nA	1.5 V	600 + 20

2002 Condensed Specifications

DC VOLTS		ACCURACY ±(ppm of reading + ppm of range)	
RANGE	RESOLUTION	INPUT RESISTANCE	90 Days
200 mV	1 nV	>100 GΩ	15 + 8
2 V	10 nV	>100 GΩ	6 + 0.8
20 V	100 nV	>100 GΩ	6 + 0.15
200 V	1 μV	10 MΩ ±1%	14 + 2
1000 V	10 μV	10 MΩ ±1%	14 + 0.4

RESISTANCE		ACCURACY ±(ppm of reading + ppm of range)	
RANGE	RESOLUTION	CURRENT SOURCE	90 Days
20 Ω	100 nΩ	7.2 mA	15 + 6
200 Ω	1 μΩ	960 μA	15 + 4
2 kΩ	10 μΩ	960 μA	7 + 0.4
20 kΩ	100 μΩ	96 μA	7 + 0.4
200 kΩ	1 mΩ	9.6 μA	29 + 0.8
2 MΩ	10 mΩ	1.9 μA	53 + 0.5
20 MΩ	100 mΩ	1.4 μA	175 + 0.6
200 MΩ	1 Ω	1.4 μA	500 + 3
1 GΩ	10 Ω	1.4 μA	2000 + 15

DC AMPS		ACCURACY ±(ppm of reading + ppm of range)	
RANGE	RESOLUTION	MAXIMUM BURDEN VOLTAGE	90 Days
200 μA	10 pA	0.25 V	275 + 25
2 mA	100 pA	0.3 V	275 + 20
20 mA	1 nA	0.35 V	275 + 20
200 mA	10 nA	0.35 V	300 + 20
2 A	100 nA	1.1 V	600 + 20

GENERAL/STANDARDS COMPLIANCE

POWER
Voltage: 90–134V and 180–264V universal self-selecting.
Frequency: 50Hz, 60Hz, or 400Hz self-identifying.
Consumption: <55 VA.

ENVIRONMENT
Operating Temperature: 0° to 50°C.
Storage Temperature: -40° to +70°C.
Humidity: 80% R.H., 0° to 35°C.
Altitude: 4,500m (15,000 ft) operating; 12,000m (40,000 ft.) non-operating.

PHYSICAL
Case Dimensions: 90mm high × 214mm wide × 369mm deep (3½ in × 8½ in × 14½ in).
Unit Weight: 4.2kg (9.2 lbs).

STANDARDS
EMI/RFI: Conforms to VDE 0871B (per Vfg 1046/1984), IEC 801-2, FCC part 15 Class B, CISPR-22 (EN55022).
Safety: Conforms to IEC348, CAN/CSC22.2 No. 231, MIL-T-28800E1.

FREQUENCY COUNTER

RANGE: 1Hz–15MHz.
ACCURACY: ±(0.03% of reading).

DC IN-CIRCUIT CURRENT

RANGE: 100μA to 12A.
ACCURACY: ±(5% + 2 counts) over 2 years.
TRACE RESISTANCE: 1mΩ to 10Ω typical.

TEMPERATURE

Built-in linearization for J, K, N, T, E, R, S, B thermocouple types to ITS-90 and 100Ω platinum RTDs.

For complete specifications, refer to the 2001 or 2002 Technical Data Book.

Model 2001 and 2002 Specifications

DIGITAL MULTIMETERS

1.888.KEITHLEY (U.S. only)

www.keithley.com

KEITHLEY

A GREATER MEASURE OF CONFIDENCE