

6½-Digit Digital Multimeters and 1.8 MS/s Isolated Digitizers

NI 4070

- 12 built-in measurement functions
- 1.8 MS/s isolated waveform acquisition
- 10 to 23-bit flexible resolution
- Built-in self-calibration
- ±300 VDC/ V_{rms} isolation
- 425 V_p AC measurements

Calibration

- Gain, temperature, and offset self-calibration
- 2-year external calibration cycle

Operating Systems

- Windows 2000/NT/XP
- LabVIEW Real-Time
- Linux

Recommended Software

- LabVIEW
- LabWindows/CVI
- SignalExpress

Driver Software (included)

- NI-DMM
- DMM Express VI for LabVIEW
- DMM Soft Front Panel



Overview

The National Instruments 4070 FlexDMM is a 6½-digit digital multimeter that achieve remarkable throughput rates while maintaining precision and stable measurement accuracy. With National Instruments proprietary FlexDMM technology, these DMMs also provide a fully isolated, high-voltage digitizer, capable of acquiring waveforms at sampling rates up to 1.8 MS/s at all voltage and current values. Using the analysis functions in National Instruments LabVIEW, you can analyze these waveforms in both the time and frequency domains. The NI 4070 DMMs have superior speed, accuracy, and functionality, making them an excellent fit for use in automated tests on both the production floor and in an R&D environment.

Digits	Resolution (Bits)	Max Sampling Rate DC Voltage and Current ¹	Reading Rate ²
7	23	5 S/s	5 S/s
6½	22	100 S/s	100 S/s
5½	18	5 kS/s	3 kS/s
4½	15	20 kS/s	10 kS/s
3	10	1.8 MS/s	–

¹Maximum sample rate refers to waveform acquisition

²Autozero disabled, except 7 digits, measured on a 10 V and 10 kΩ range

Table 1. NI 4070 Key Specifications

High-Speed Digital Multimeter

1.8 MS/s Flexible-Resolution Isolated Digitizer

- Users can vary the resolution of the FlexDMM from 10 to 23 bits by simply changing the sampling rate, as reflected in Figure 1.
- The unique multi-instrument functionality minimizes overall system cost by eliminating the need to purchase a separate data acquisition device, signal conditioning, fixturing, and so on.

Built-In Self-Calibration and 2-Year Calibration Cycle

- Self-calibration (Self-Cal) improves accuracy by removing errors due to temperature variation and long-term drift.
- Self-Cal ensures accuracy over entire 0 to 55 °C operating range.
- 2-year external calibration cycle reduces downtime and maintenance costs.

Software

- NI-DMM is an IVI-compliant driver that accesses the complete functionality of the DMM through an easy-to-use application programming interface (API).
- Compatible languages include C/C++, .NET, Visual Basic, LabVIEW, and LabWindows/CVI.




Figure 1. NI 4070 FlexDMM Resolution versus Sample Rate

Ordering Information

NI PCI-4070.....778275-01
 NI PXI-4070.....778274-01

Includes the P-1 Probe Set, NI-DMM, DMM Express VI, and DMM Soft Front Panel.

Recommended Switching and Accessories

NI PXI-2527
 300 V multiplexer switch 778572-27
 NI PXI-2530
 128x1 multiplexer switch.....778660-01
 P-1 Probe Set (standard probe)761000-01
 P-2 Probe Set (additional probe)184698-01
 P-3 Probe Set (banana plug to bare wire)185692-01
 10 A current shunt, CSM-10A777488-02

BUY NOW!

For complete product specifications, pricing, and accessory information, call (800) 813 3693 (U.S.) or go to ni.com/modularinstruments.



6½-Digit Digital Multimeters and 1.8 MS/s Isolated Digitizers

Specifications

Specifications subject to change without notice.

For the most current and complete specifications, visit ni.com/modularinstruments.

DC Functions

DC Voltage ±(ppm of reading + ppm of range)

Range	Resolution	Input Resistance	24 Hr Tcal ±1 °C	90-Day Tcal ±5 °C	2-Year Tcal ±5 °C	Tempco/°C	
						Without Self-Cal	With Self-Cal
100 mV	100 nV	>10 GΩ, 10 MΩ	10 + 10	30 + 20	40 + 20	4 + 5	0.3 + 0.3
1 V	1 μV	>10 GΩ, 10 MΩ	6 + 2	20 + 6	25 + 6	2 + 1	0.3 + 0.3
10 V	10 μV	>10 GΩ, 10 MΩ	4 + 2	20 + 6	25 + 6	1 + 1	0.3 + 0.3
100 V	100 μV	10 MΩ	6 + 2	30 + 6	35 + 6	4 + 1	0.3 + 0.3
300 V	1 mV	10 MΩ	6 + 6	30 + 20	35 + 20	4 + 3	0.3 + 0.3

DC Current ±(ppm of reading + ppm of range)

Range	Resolution	Burden Voltage (typical)	Noise (ppm of range rms)	2-Year	Tempco/°C
20 mA	10 nA	<20 mV	20	400 + 75	8 + 1
200 mA	100 nA	<200 mV	3	400 + 20	8 + 0.2
1 A	1 μA	<800 mV	3	500 + 20	8 + 0.4

Resistance (4-wire and 2-wire) ±(ppm of reading + ppm of range)

Range	Resolution	Test Current	Max Test Voltage	24 Hr Tcal ±1 °C	90-Day Tcal ±5 °C	2-Year Tcal ±5 °C	Tempco/°C	
							Without Self-Cal	With Self-Cal
100 Ω	100 μΩ	1 mA	100 mV	15 + 10	50 + 10	80 + 10	8 + 1	0.8 + 1
1 kΩ	1 mΩ	1 mA	1 V	12 + 2	50 + 3	80 + 3	8 + 0.1	0.8 + 0.1
10 kΩ	10 mΩ	100 μA	1 V	12 + 2	50 + 3	80 + 3	8 + 0.1	0.8 + 0.1
100 kΩ	100 mΩ	10 μA	1 V	15 + 2	50 + 6	80 + 6	8 + 0.5	0.8 + 0.5
1 MΩ	1 Ω	10 μA	10 V	20 + 2	60 + 10	90 + 10	8 + 1	0.8 + 1
10 MΩ	10 Ω	1 μA	10 V	100 + 2	200 + 10	400 + 10	30 + 3	30 + 3
100 MΩ	100 Ω	1 μA 10 MΩ	10 V	900 + 20	1,800 + 40	2,000 + 40	200 + 10	200 + 10

Diode Test

Range	Resolution	Test Current	Accuracy
10 V	10 μV	1 μA, 10 μA, 100 μA, 1 mA	Add 20 ppm of reading to 10 V DC voltage specifications

AC Functions

Digits	Reading Rate	Bandwidth
6½	0.25 S/s	1 Hz to 300 kHz
6½	2.5 S/s	10 Hz to 300 kHz
6½	25 S/s	100 Hz to 300 kHz
6½	100 S/s	400 Hz to 300 kHz
5½	1.0 kS/s	20 to 300 kHz

AC Voltage 2-year ± (% of reading + % of range), 23 ±5 °C

Range (rms)	Peak Voltage	Resolution	1 to 40 Hz	40 Hz to 20 kHz	20 to 50 kHz	50 to 100 kHz	100 to 300 kHz
50 mV	±105 mV	100 nV	0.1 + 0.04	0.05 + 0.04	0.09 + 0.04	0.5 + 0.08	3 + 0.1
500 mV	±1.05 V	1 μV	0.1 + 0.01	0.05 + 0.02	0.09 + 0.02	0.5 ± 0.02	3 + 0.05
5 V	±10.5 V	10 μV					
50 V	±105 V	100 μV					
300 V	±450 V	1 mV					
Tempco/°C			0.001 + 0.001	0.001 + 0.001	0.001 + 0.001	0.001 + 0.001	0.01 + 0.01

6½-Digit Digital Multimeters and 1.8 MS/s Isolated Digitizers

AC Current 2-Year ±(% of reading + % of range)

Range (rms)	Peak Current	Resolution	Burden Voltage (rms)	1 Hz to 20 kHz	Tempco/°C
10 mA	±20 mA	10 nA	<10 mV	0.04 + 0.02	0.001 + 0.0001
100 mA	±200 mA	100 nA	<100 mV	0.04 + 0.02	0.001 + 0.0001
1 A	±2 A	1 µA	<800 mV	0.1 + 0.02	0.001 + 0.0001

Frequency and Period

Input Range	Frequency Range	Period Range	Resolution	2-Year Accuracy % of Reading
50 mV to 300 V	1 Hz to 500 kHz	1 s to 2 µs	6½ digits	0.01

Isolated Digitizer Mode

Acquisition System

Available sample rates	$\frac{1.8 \text{ MS/s}}{n}$, where n = 1, 2, 3, ... 1.8 x 10 ⁵
Variable resolution	10 to 23 bits
Available functions	Voltage and current
Voltage ranges	±100 mV to ±300 V (DC or AC coupled)
Current ranges	20 mA to 1 A

DC Voltage ±(ppm of reading + ppm of range)

Range	Input Impedance	Flatness Error (20 kHz)	Bandwidth (-3 dB)	THD 1 kHz Signal (-1 dBfs)	THD 1 kHz Signal (-1 dBfs)
100 mV	>10 GΩ, 1 MΩ	-0.03 dB	300 kHz	-104 dB	-78 dB
1 V	>10 GΩ, 1 MΩ	-0.03 dB	300 kHz	-109 dB	-83 dB
10 V	>10 GΩ, 1 MΩ	-0.03 dB	300 kHz	-96 dB	-70 dB
100 V	1 MΩ	-0.03 dB	300 kHz	-96 dB	-70 dB
300 V	1 MΩ	-0.03 dB	300 kHz	-98 dB	-72 dB

DC Current ±(ppm of reading + ppm of range)

Range	Resolution	Burden Voltage (typical)	Flatness Error (20 kHz)	Bandwidth (-3 dB)
20 mA	10 nA	<20 mV	±0.01 dB	430 kHz
200 mA	100 nA	<200 mV	±0.01 dB	430 kHz
1 A	1 µA	<800 mV	±0.01 dB	400 kHz

Certifications and Compliance

Safety

IEC 61010-1; EN 61010-1; UL 61010-1; CAN/CSA C22.2 No. 61010-1

Installation Category..... II

Pollution Degree 2

Electromagnetic Compatibility

Emissions EN 55011 Class A at 10 m FCC Part 15A above 1 GHz

Immunity Evaluated to EN 61326:1997 + A2: 2001, Table 1

EMC/EMI..... CE, C-Tick and FCC Part 15 (Class A) Compliant

NI Services and Support



NI has the services and support to meet your needs around the globe and through the application life cycle – from planning and development through deployment and ongoing maintenance. We offer services and service levels to meet customer requirements in research, design, validation, and manufacturing. Visit ni.com/services.

Training and Certification

NI training is the fastest, most certain route to productivity with our products. NI training can shorten your learning curve, save development time, and reduce maintenance costs over the application life cycle. We schedule instructor-led courses in cities worldwide, or we can hold a course at your facility. We also offer a professional certification program that identifies individuals who have high levels of skill and knowledge on using NI products. Visit ni.com/training.

Professional Services

Our Professional Services Team is comprised of NI applications engineers, NI Consulting Services, and a worldwide National Instruments Alliance Partner program of more than 600 independent consultants and

integrators. Services range from start-up assistance to turnkey system integration.

Visit ni.com/alliance.



OEM Support

We offer design-in consulting and product integration assistance if you want to use our products for OEM applications. For information about special pricing and services for OEM customers, visit ni.com/oem.

Local Sales and Technical Support

In offices worldwide, our staff is local to the country, giving you access to engineers who speak your language. NI delivers industry-leading technical support through online knowledge bases, our applications engineers, and access to 14,000 measurement and automation professionals within NI Developer Exchange forums. Find immediate answers to your questions at ni.com/support.

We also offer service programs that provide automatic upgrades to your application development environment and higher levels of technical support. Visit ni.com/ssp.

Hardware Services

NI Factory Installation Services

NI Factory Installation Services (FIS) is the fastest and easiest way to use your PXI or PXI/SCXI combination systems right out of the box. Trained NI technicians install the software and hardware and configure the system to your specifications. NI extends the standard warranty by one year on hardware components (controllers, chassis, modules) purchased with FIS. To use FIS, simply configure your system online with ni.com/pxiadvisor.

Calibration Services

NI recognizes the need to maintain properly calibrated devices for high-accuracy measurements. We provide manual calibration procedures, services to recalibrate your products, and automated calibration software specifically designed for use by metrology laboratories. Visit ni.com/calibration.

Repair and Extended Warranty

NI provides complete repair services for our products. Express repair and advance replacement services are also available. We offer extended warranties to help you meet project life-cycle requirements. Visit ni.com/services.



ni.com • (800) 813 3693

National Instruments • info@ni.com

